

Product information sheet

- Product Name: **Rubber Speed Bumps 3" thick**
- Models: 6', 4' long
- Manufacturer: GNR Technologies Inc., manufacturing division of Traffic Logix Inc.
990 Upton, Lasalle, QC H8R 2T9
Tel.: (514) 366-6116, Fax: (514) 366-6440
- Product Description:
1. Material: compression molded composite of the 100% recycled rubber and polyurethane prepolymer
 2. Physical properties of the rubber composite:
 - a) Density 0.6 oz/cu in (ASTM C642)
 - b) Durometer Hardness 70A ± 7 (ASTM D2240)
 - c) Tensile Strength 300 psi (ASTM D412)
 - d) Compression deformation 7% at 70psi, 68°F (ASTM D575)
 - e) Brittleness at Low temperature: -40°F (ASTM D746)
 - f) Freeze and thaw when exposed to deicing chemicals no loss after 50 cycles (ASTM C672)
 - f) Coefficient of thermal expansion: 8×10^{-5} in/in/°F (ASTM C531)
 - g) Weathering 70 hours at 158°F (ASTM D573)
 - hardness retained 100% (± 5%)
 - compressive strength 100% (± 5%)
 - tensile strength 100% (± 5%)
 - elongation retained 100% (± 5%)
 3. Available models: 6', 4' long
 4. Basic dimensions and nominal weights as per attached drawing for 6' model
 5. Finishing: Black with durable reflective yellow tape as per attached drawing
- Installation method: installation with spikes 14" long (minimum diameter ½")
- 4 spikes for 6' model
 - 3 spikes for 4' model
- Components:
- a) 100% recycled rubber from car and truck tires (NR, SBR)
 - b) polyurethane prepolymer for rubber granules
 - c) cat's eyes reflectors
 - d) molded in a durable yellow, reflective tape covered with the glass beads
- Attached Drawings: 6' model, drawing No. 6SB10
14" rebar spike, drawing No. 05SP01