

**MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS & RELATED MATERIALS**

**SECTION I
PRODUCT IDENTIFICATION**

Manufacturer: Ennis Paint, Inc. Information Ph: 800-331-8118
P.O. Box 404 Emergency Ph: 800-424-9300
Ennis, Texas 75120 Revised: 5/17/05

Product Class: ~~High Solids~~ Waterborne
Lead Free Fast Dry Traffic Paint - APPLIES TO ALL COLORS

Trade Name: Ennis Paint
C.A.S. Number: N/A - Mixture
VOC: < 150 G/L
Specific Gravity: 1.6-1.7

HAZARD RATINGS:		HTH	1
NONE-EXTREME		FIRE	1
0 - 4		REACTIVITY	0
		PERSONAL PROTECTION	0

**SECTION II
HAZARDOUS INGREDIENTS**

INGREDIENTS	CAS #	WEIGHT -----		Exposure Limits -----		VP
		%	ACGIH/TLV	OSHA/PEL		mm HG
Methanol	67-56-1	2.5 MAX	200 ppm	200 ppm		97.7
		STEL =		250 ppm		@ 68F

**SECTION III
PHYSICAL DATA**

BOILING RANGE: 147-477°F VAPOR DENSITY: Heavier than Air.
EVAPORATION RATE: 0.45 x n-Butyl Acetate LIQUID DENSITY: 1.5-1.7 kg/l @ 20°C
APPEARANCE: Heavy Liquid V.O.C. < 150 g/l / 1.3 lbs/gal
VOLATILES: VOL % 38-40% WGT % 20-25%

**SECTION IV
FIRE AND EXPLOSION HAZARD DATA**

FLAMMABILITY CLASS: Not Flammable FLASHPOINT: ASTM D 3278: >201°F TCC LEL: N/A UEL: N/A
ASTM D 93: >201°F

EXTINGUISHING MEDIA:

- NONE

SPECIAL FIREFIGHTING PROCEDURES:

- NONE

UNUSUAL FIRE & EXPLOSION HAZARDS:

- KEEP CONTAINERS TIGHTLY CLOSED.
- ISOLATE FROM HEAT, SPARKS AND OPEN FLAME.
- CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.
- THIS MATERIAL WILL NOT BURN UNTIL THE WATER HAS EVAPORATED. DRIED RESIDUE CAN BURN.
- IN A TEST "EVALUATION OF THE FIRE HAZARD OF WATER-BORNE COATINGS" (FACTORY MUTUAL RESEARCH CORPORATION SCIENTIFIC CIRCULAR 804 DECEMBER 1977), FOUR WATER-BORNE COATINGS "PRESENTED NO [FIRE] HAZARD". "IT WAS ALSO CONCLUDED THAT RESULTS OBTAINED FROM LABORATORY [FLASH POINT] TESTS ARE NOT REPRESENTATIVE INDICATION OF THE FIRE HAZARD OF WATER-BORNE COATINGS".

SECTION V HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL:

- SEE SECTION II FOR INFORMATION ABOUT INDIVIDUAL INGREDIENTS.

EFFECTS OF OVEREXPOSURE:

- SEVERE EYE IRRITATION.
- HEADACHES, DIZZINESS AND/OR NAUSEA. SKIN CONTACT MAY CAUSE IRRITATION OR RASH.
- SKIN ABSORPTION MAY POTENTIALLY CONTRIBUTE TO THE OVERALL EXPOSURE OF METHANOL. APPROPRIATE MEASURES SHOULD BE TAKEN TO PREVENT ABSORPTION SO THAT THE TLV IS ALWAYS MET.
- NIOSH RECOMMENDS A LIMIT OF 200 ppm, 8-HOUR TWA; 800 ppm 15-MINUTE CEILING FOR METHANOL.
- OVEREXPOSURE TO METHANOL (OR ITS COMPONENTS) HAS BEEN SUGGESTED AS A CAUSE OF EYE DAMAGE IN HUMANS.

FIRST AID:

- **EYES:** FLUSH THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES, LIFTING UPPER AND LOWER LIDS OCCASIONALLY. GET IMMEDIATE MEDICAL ATTENTION.
- **SKIN:** WASH EXPOSED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. IF IRRITATION OCCURS, GET MEDICAL ATTENTION.
- **INHALATION:** MOVE VICTIM AWAY FROM SOURCE OF EXPOSURE AND INTO FRESH AIR. IF SYMPTOMS OF EXPOSURE DEVELOP, GET MEDICAL ATTENTION.

SECTION VI REACTIVITY DATA

STABILITY: ☐ UNSTABLE ☒ STABLE
HAZARDOUS POLYMERIZATION: ☐ MAY OCCUR ☒ WILL NOT OCCUR
INCOMPATIBILITY: N/A
CONDITIONS TO AVOID: N/A
HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

- COLLECT IN A RETAINING AREA OR CLOSED CONTAINER IF POSSIBLE, AVOID EXCESS DILUTION WITH WATER.
- MATERIAL MAY BE CONTAINED WITH AN ABSORBENT MATERIAL THEN TRANSFERRED TO AN APPROPRIATE CONTAINER.
- AVOID EXPOSURE TO HEAT, SPARKS, FIRE OR OPEN FLAME.
- AVOID HOT METAL SURFACES.

WASTE DISPOSAL METHOD:

- DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.
- AVOID DISCHARGE INTO NATURAL WATERS.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:

- WEAR APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING SPRAYING APPLICATION TO PROTECT AGAINST OVERSPRAY.

VENTILATION:

- ADEQUATE VENTILATION IS NECESSARY WHEN SPRAYING OR MIXING AND EXHAUST WITH PROPER AIRFLOW IS ALWAYS RECOMMENDED.
- AVOID ANY DIRECT INHALATION OF SPRAY MIST IF THIS PRODUCT IS SPRAYED.

PROTECTION GLOVES:

- RECOMMENDED

EYE PROTECTION:

- CLOSE FITTING SAFETY GOGGLES.

OTHER PROTECTIVE EQUIPMENT:

- MAY ADHERE TO SKIN - GLOVES, LONG SLEEVES, HATS AND FACE SHIELDS ARE RECOMMENDED.
- PROTECTIVE CREAMS MAY HELP, BUT ARE NOT AS PROTECTIVE AS GLOVES, ETC.
- TRAIN AND EDUCATE EMPLOYEES IN THE SAFE USE OF THE PRODUCT.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

- PROTECT FROM FREEZING

SECTION X ECOLOGICAL INFORMATION

ECOTOXICITY: FISH: FATHEAD MINNOW: 96 HR; LC50 = >750 mg/L
OTHER: NO OTHER INFORMATION IS AVAILABLE

SECTION XI ADDITIONAL REGULATORY INFORMATION

THIS PRODUCT IS NOT REGULATED BY D.O.T. WHEN SHIPPED DOMESTICALLY BY LAND.

SARA TITLE III SECTION 313:

THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT OF 1986 AND OF 40 CFR 372:

CAS#	CHEMICAL NAME	PERCENT BY WEIGHT
67-56-1	METHANOL	2.5 MAX

PROP 65 (CARCINOGEN):

WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

CAS#	CHEMICAL NAME	PERCENT BY WEIGHT
	NONE	

PROP 65 (TERATOGEN):

WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

CAS#	CHEMICAL NAME	PERCENT BY WEIGHT
	NONE	

PROP 65 (BOTH CARCINOGEN AND TERATOGEN):

WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER OR BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

CAS#	CHEMICAL NAME	PERCENT BY WEIGHT
	NONE	

TSCA-U.S. TOXIC SUBSTANCES CONTROL ACT:

ALL COMPONENTS OF THIS MIXTURE ARE IN COMPLIANCE WITH THE INVENTORY LISTING REQUIREMENTS OF THE U.S. TOXIC SUBSTANCES CONTROL ACT (TSCA) CHEMICAL SUBSTANCES INVENTORY.

SECTION XII
MISCELLANEOUS INFORMATION

THE INFORMATION OFFERED HEREIN IS, TO THE BEST OF OUR KNOWLEDGE, TRUE AND ACCURATE, BUT ALL RECOMMENDATIONS ARE MADE WITHOUT WARRANTY, EXPRESS OR IMPLIED, SINCE THE CONDITIONS OF USE ARE BEYOND OUR CONTROL, NEITHER ENNIS PAINT, INC., NOR ITS AGENTS SHALL BE LIABLE FOR ANY INJURY, LOSS OR DAMAGE, DIRECT OR CONSEQUENTIAL, ARISING FROM THE USE OR THE INABILITY TO USE THE PRODUCT DESCRIBED HEREIN. NO PERSON IS AUTHORIZED TO MAKE ANY STATEMENT OR RECOMMENDATION NOT CONTAINED IN THE MATERIAL DATA SHEET, AND ANY SUCH STATEMENT OR RECOMMENDATION, IF MADE SHALL NOT BIND THE CORPORATION.